

Specialized Construction Products EzStop

NZ_DA02931

Part A	19RX5021-20KG	Approvals	Used as part of a BRANZ appraised system.
---------------	---------------	------------------	---

Product Overview

Specialized Construction Products EzStop is a mix of aggregates; cements, proprietary ingredients and fibre combined to produce a cement based stopping compound.

Features And Benefits

- Cement based stopping compound
- Fine aggregate mix
- Very good adhesion to EZ Panels
- Excellent levelling and smoothness prior to plastering


Uses And Typical Specifications

Uses EzStop is a polymer modified cement based patching (Stopping) compound used in Specialized EzPanel (AAC) systems to prefill imperfections and gaps ahead of application of levelling and texture coating systems. Also used to repair broken corners, chips and dings.

Performance Guide

Weather	Excellent weather resistance when used as part of an approved Specialized Construction Products system.	Heat Resistance	Up to 60°C
Water	Resists rain and condensation when used as part of an approved Specialized Construction Products system.	Solvent	Solvent resistant
Abrasion	Resists abrasion when used as part of an approved Specialized Construction Products system.		

Typical Properties

V.O.C Content	<1 g/L	Full Cure (25C, 50% R.H)	24 Hours
Clean Up	Water - immediately after use.	Sizes	20kg
Application Method	 Trowel		
Application Conditions	<p>Solids By Volume 100</p> <p>Min Max</p> <p>Wet Film Per Coat (microns)</p> <p>Dry Film Per Coat (microns)</p> <p>Recoat Time (min)</p> <p>Theoretical Spread Rate (m²/L)</p> <p style="text-align: right;">Recommended</p>		
Typical Properties Notes	Curing time of EzStop will vary due to ambient temperature, relative humidity, surface temperature, surface porosity, application methods, and/or the thickness of the material. Although this plaster contains cement and will not fully cure for 28 days; finish coats can be applied after a minimum drying time of approximately 48 hours at 20°C.		

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> The substrate to which EzStop is to be applied must be installed in strict accordance with the manufacture's specifications and recommended installation procedures. For concrete/masonry substrates the suppliers required curing time must be allowed after installation to ensure the joints in the substrate have completed cured, shrunk, and stabilized. All solid concrete substrates must be fully cured and dry. New concrete must be at least 21 days old prior to the application of any render product. <p>All nibs, protrusions and excess mortar on the surface of the bricks or irregularities in the slab must be ground off prior to rendering.</p> <p>All surfaces must be clean and free of debris, dirt and dust, efflorescence, grease, oils, curing agents, cleaning solutions, mould and algae or any other contaminants that may affect adhesion. Deeply contaminated substrates must be abraded to provide a clean sound surface. All loose or damaged material must be removed by water blasting, captive shot blasting, or mechanical wire brushing and then washed down before rendering commences.</p> <p>Painted or glossy surfaces such as power floated concrete must be specially primed, acid etched or mechanically abraded prior to the application of any render.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> MIXING: Add approximately 5.5 litres of clean water to a clean bucket and then while stirring slowly add the 20kg bag of EzStop should be mixed with a heavy-duty electric drill powering a high shear stirrer at approximately 600 r.p.m. The product should be mixed for a minimum of 2 minutes or long enough to provide a smooth lump-free blend. The consistency should be such that the material holds its shape when a finger is run through the surface. Let the mix stand for 5 minutes and give it a quick re-stir before application and adjust the final consistency. <p>Once the EZpanels have been correctly fixed, a two metre straight edge should be used to check the flatness of the walls surface. DuraRasp should be used to sand off any large irregularities. Deviations and holes in the surface of the EZpanels should be filled with EZstop plaster and screeded flat. Only once the walls are flat and true and have been well stopped should mesh coating commence.</p> <p>Apply render only when the temperature is between 5°C and 30°C.</p> <p>For full system details refer to the Specialized installation guide.</p>

Health And Safety			
MSDS Number	DLX003960	Using Safety Precautions	For detailed information refer to product label and the current Material Safety Data Sheet available through Specialized Construction Products Sales and Customer Service Offices.
MSDS Link	https://go.lupinsys.com/duluxgroup/harms/pm/298068024bbe13c459fca061fef272c5-published/attachment/nz-sds.pdf		
Health Effects	Causes severe skin burns and eye damage. May cause respiratory irritation.	Protective Equipment	Wear safety shoes, overalls, gloves, safety glasses, dust mask.
Storage	Keep out of reach of children. Store for no longer than 6 in a dry, well-ventilated area and off the floor. Product must be protected from the weather and from mechanical damage. Store away from foodstuffs.	Disposal	Do not contaminate storm-water with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Check with your local council first.
Handling	Avoid eye and skin contact. Avoid inhalation of dust.		
In the case of emergency, please call 0800 734 607			

Precautions And Limitations
<p>Ensure all surface preparation instruction are followed.</p> <p>All freshly applied material must be weather protected for a minimum of 24 hours after application. Exposure of applied product to rain, snow, dew, or other inclement weather conditions, direct hard sunlight or sources of heat while it is curing may have a detrimental effect on the finish.</p> <ul style="list-style-type: none"> DO NOT over-water, over mix, or remix aged EzStop with additional water. DO NOT mix more EzStop than you can use in 45 minutes. DO NOT use EzStop that has been mixed for more than one hour. DO NOT apply EzStop to wooden surfaces. DO NOT apply EzStop over wet, frozen or frost affected surfaces. DO NOT apply EzStop where it will be subjected to permanent immersion or where ponding will occur. DO NOT reactivate EzStop with water once it has begun to set. DO NOT wet the substrate prior to the application of EzStop. DO NOT apply EzStop unless the substrate has been properly cleaned, primed and prepared.

Transport And Storage			
Pack A	19RX5021	Shipment Name	Not dangerous goods. No special transport requirements.
Size 20kg	Weight 20kg		
Flash Point	N/A	UN Number	N/A
Dangerous Goods Class	N/A	Package Group	N/A

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118